





POWER

Engine 2-stroke single with exhaust power valve, liquid-cooled

10.2:1 (low speed) - 8.7:1 (high speed)

Displacement 99cc

Bore x Stroke 52.5 x 45.8mm

Compression

Ratio

28mm Keihin carburetor

Fuel System

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes Single 220mm petal disc with dual-piston caliper **Rear Brakes** Single 220mm petal disc with single-piston caliper

DETAILS

Rear Tire

High-tensile steel perimeter design **Frame Type** withsubframe member

90/100-16

29° /4.3 in Rake/Trail

Overall Length 75.6 in

Overall Width 30.1 in

Overall Height 45.3 in

Clearance

Ground

13.0 in

Seat Height 34.3 in

Curb Weight 169.7 lb*

Fuel Capacity 1.32 gal

Wheelbase 51.6 in

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front Suspension / **Wheel Travel** 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / **Wheel Travel** Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in

Front Tire

70/100-19



