
MULE PRO-FXT™ EPS CAMO









POWER

4-stroke, 3-cylinder, DOHC, liquid-cooled, gas **Engine**

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.2 in

Fuel Capacity

Cargo Bed Load

Capacity

Turning Radius 16.0 ft

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-**Cargo Bed Dimensions (LxWxH)**

person)

7.9 gal

models) 1616 lb (1264 lb California model) **Payload Capacity**

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights, (2) Auxiliary LED headlights, (2)

Halogen tail/brake lights

CAPABILITY

Wheel Travel

Double wishbone/8.7 in Front Suspension / **Wheel Travel**

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in **Overall Height** 77.6 in **Curb Weight** 1916.1 lb* Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

> 1000 lb (3-person)350 lb (6-person)(600 lb for California

reminder lamps

Color Choices Realtree Xtra® Green Camo

Kawasaki 3-Year Limited Warranty Warrantv

Scan with camera to view videos, key features and more.

