
MULE PRO-FXT™ RANCH EDITION









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.0 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

Cargo Bed Load 1000 lb (3-person)350 lb (6-person)(600 lb for California

models) Capacity

Payload Capacity 1567.8 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights, (2) Auxiliary LED headlights, (2)

Halogen tail/brake lights

CAPABILITY

Double wishbone/8.7 in Front Suspension / Wheel Travel

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in **Wheel Travel**

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

DETAILS

Overall Length 135.6 in **Overall Width** 64.0 in **Overall Height** 79.5 in **Curb Weight** 1971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Metallic Phantom Silver: \$17,199, Metallic Rustic Bronze:

Kawasaki 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

