## <sup>2021</sup> **Z900 ABS**





METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK

PEARL BLIZZARD WHITE/METALLIC SPARK BLACK



## POWEREngine4-stroke, 4-cylinder, DOHC, 16-valve, liquid-<br/>cooledDisplacement948ccBore x Stroke73.4 x 56.0mm

Compression Ratio	11.8:1
Maximum Torque	73.1 lb-ft @ 7,700 rpm
Fuel System	DFI® with 36mm Keihin throttle bodies
Ignition	TCBI with electronic advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Integrated Riding Modes, Kawasaki Traction Control (KTRC), Power Modes (2)

## PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted fork with rebound damping and spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link, stepless rebound damping, adjustable spring preload/5.5 in
Front Tire	120/70 ZR17

Rear Tire	180/55 ZR17
Front Brakes	Dual 300mm petal-style discs with four-piston calipers, ABS
Rear Brakes	Single 250mm petal-style disc, ABS

## DETAILS

	Frame Type	Trellis, high tensile steel
	Rake/Trail	24.9°/4.3 in
	Overall Length	81.5 in
	Overall Width	32.5 in
	Overall Height	42.5 in
	Ground Clearance	5.7 in
	Seat Height	31.5 in
	Curb Weight	467.5 lb*
	Fuel Capacity	4.5 gal
	Wheelbase	57.3 in
d	Special Features	Rideology the App Smartphone Connectivity, TFT Instrumentation
	Color Choices	Pearl Blizzard White / Metallic Spark Black, Metallic Spark Black / Metallic Flat Spark Black
	Warranty	12 Month Limited Warranty





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit venezuela.kawasaki-la.com for full product details.