## KLX<sup>®</sup>230 ABS







4.10 x 18

D	N	W	I E	D
Г	U	W	ľ	л

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

## **DETAILS**

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

Frame Type High-tensile steel, box-section perimeter

Single 265mm petal disc with a dualpiston caliper with Dual Purpose ABS

Single 220mm petal disc with single-

piston caliper with Dual Purpose ABS

Rake/Trail 27.5°/4.6 in

Overall Length 82.9 in.

Overall Width 32.9 in.

Overall Height 45.9 in.

Clearance

Ground

Seat Height 34.8 in.

**Curb Weight** 293.3 lb. / 295.5 lb. CA model\*

10.4 in.

Fuel Capacity 2.0 gal.

Wheelbase 54.3 in.

**Color Choices** Lime Green

Warranty 12 Months

## **PERFORMANCE**

Suspension / Wheel Travel

Rear

37mm telescopic fork/8.7 in
Uni-Trak® linkage system ar

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

**Front Tire** 2.75 x 21



Suspension /

**Wheel Travel** 

