## <sup>2021</sup> KLX<sup>®</sup>230R S







100/100-18

## POWER

T OWER		Front Brakes	Single 240mm petal disc with a dual-
Engine	4-stroke single, SOHC, air-cooled		piston caliper
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper
Bore x Stroke	67.0 x 66.0mm		
Compression Ratio	9.4:1	DETAILS	
Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter
Ignition	TCBI Electronic Advance	Rake/Trail	25.7°/4.3 in
Transmission	6-speed, return shift with wet multi-disc	<b>Overall Length</b>	80.1 in
mansmission	manual clutch	Overall Width	33.1 in
Final Drive	Chain	Overall Height	46.3 in
PERFORMANCE		Ground Clearance	10.8 in
Front	37mm telescopic fork/8.7 in	Seat Height	35.4 in
Suspension / Wheel Travel		Curb Weight	253.6 lb / 262.3 lb. (50 State)*
Rear	Uni-Trak <sup>®</sup> linkage system and single shock	Fuel Capacity	1.7 gal
Suspension / Wheel Travel	with adjustable spring preload/8.8 in	Wheelbase	53.1 in
Front Tire	80/100-21	<b>Color Choices</b>	Lime Green

**Rear Tire** 

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit venezuela.kawasaki-la.com for full product details.

Warranty

6 Months

