







D	n	V	V	D
Г	u	V	v	П

Engine 2-stroke single with exhaust power valve, liquid-cooled

Displacement 84cc

**Bore x Stroke** 48.5 x 45.8mm

**Compression Ratio** 

**Fuel System** 

28mm Keihin carburetor

Ignition

CDI with digital advance

**Transmission** 

6-speed, return shift, with wet multi-disc

10.9:1 (low speed) - 9.0:1 (high speed)

manual clutch

**Final Drive** 

Chain

## **PERFORMANCE**

Front Suspension / Wheel Travel 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

**Front Tire** 

70/100-17

Rear Tire	90/100-14
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 184mm petal disc with single-piston

## **DETAILS**

Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29°/3.8 in
Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Ground Clearance	11.4 in
Seat Height	32.7 in
Curb Weight	165.3 lb*
Fuel Capacity	1.32 gal
Wheelbase	49.8 in
Color Choices	Lime Green
Warranty	Not Available



