2021 **KX**[™]85







POWER

| Engine | 2-stroke single with exhaust power valve, liquid-cooled | |
|----------------------|--|--|
| Displacement | 84cc | |
| Bore x Stroke | 48.5 x 45.8mm | |
| Compression Ratio | 10.9:1 (low speed) - 9.0:1 (high speed) | |
| Fuel System | 28mm Keihin carburetor | |
| Ignition | CDI with digital advance | |
| Transmission | 6-speed, return shift, with wet multi-disc manual clutch | |
| Final Drive | Chain | |
| | | |

Rear Tire 90/100-14 **Front Brakes** Single 220mm petal disc with dual-piston caliper Single 184mm petal disc with single-piston **Rear Brakes** caliper

DETAILS

| ed) | | |
|--------------------|---------------------|--|
| -, | Frame Type | High-tensile steel perimeter design with subframe member |
| | Rake/Trail | 29°/3.8 in |
| ti-disc | Overall Length | 72.0 in |
| | Overall Width | 30.1 in |
| | Overall Height | 43.3 in |
| | Ground Clearance | 11.4 in |
| e fork /10.8 in | Seat Height | 32.7 in |
| | Curb Weight | 165.3 lb* |
| 1 24-way | Fuel Capacity | 1.32 gal |
| | Wheelbase | 49.8 in |
| | Color Choices | Lime Green |
| | Warranty | Not Available |

PERFORMANCE

| Front Suspension / Wheel Travel | 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in |
|---------------------------------------|---|
| Rear Suspension / Wheel Travel | Uni-Trak [®] single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in |
| Front Tire | 70/100-17 |





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit venezuela.kawasaki-la.com for full product details.