MULE[™] 4000







POWER

Engine 4-stroke, 2-cylinder, OHV 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Ground Clearance

ance 7.5 in

Drum

Fuel Capacity 6.3 gal

Turning Radius 11.0 ft

Cargo Bed Dimensions

Rear Brakes

46.3 x 51.6 x 11.4 in

(LxWxH)

Cargo Bed Load 800 lb

Capacity

Payload Capacity 1327 lb

Seating Capacity

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / Ma Wheel Travel

MacPherson Strut/3.9 in

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires

23x11.00-10

Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1338.4 lb*

Wheelbase 73.6 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Dark Royal Red

Warranty Kav

Kawasaki 3-Year Limited Warranty



