MULE 4000 TRANS™









POWER

4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled **Engine**

Displacement 617cc

Maximum Torque

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive

differential lock

Engine Braking Nο

(max)

34.7 lb-ft @ 2500 rpm

2WD, shaft. Dual mode rear differential with

Alternator Output

23 amp

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Electric Power Steering (EPS)

Park Brake Type

Steering

Independent, Mechanical Drum

Front Brakes Drum **Rear Brakes** Drum

Ground Clearance 7.7 in

Fuel Capacity 6.3 gal **Turning Radius** 12.8 ft

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-**Cargo Bed**

800 lb (2-person)400 lb (4-person)

Dimensions (LxWxH)

1330 lb

Cargo Bed Load Capacity

Payload Capacity

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Warrantv Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

