MULE 4000 TRANS™









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 23

(max)

illierentiat to

23 amp

23 amp

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 7.7 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

 Cargo Bed
 50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-person)

 Dimensions (LxWxH)
 (2-person)30.3 x 47.6 x 11.2 in (4-person)

800 lb (2-person)400 lb (4-person)

Capacity

Payload Capacity 1330 lb Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

58.5 in

DETAILS

Overall Width

Cargo Bed Load

Overall Length 128.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

