## **MULE™ 4010 4x4**









## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Turning Radius

Cargo Bed
Dimensions
(LxWxH)

Cargo Bed Load
Capacity

**Rear Brakes** 

**Fuel Capacity** 

**Ground Clearance** 

800 lb

Drum

6.9 in

6.3 gal

11.2 ft

46.3 x 51.6 x 11.4 in

Payload Capacity 1327 lb

Seating Capacity 2

Towing Capacity 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

## **DETAILS**

Overall Length 116.7 in
Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1433.3 lb\*

Wheelbase 73.6 in

75.0 11

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

