## **MULE™ 4010 TRANS4x4®**









## **POWER**

4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled **Engine** 

Displacement 617cc

**Maximum Torque** 34.7 lb-ft @ 2500 rpm

**Bore x Stroke** 2.99x2.68 in

**Compression Ratio** 10:3:1

**Fuel System** DFI® with 34mm Mikuni throttle body

**Transmission** Continuously Variable Transmission (CVT) with

(H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

**Engine Braking** 

**Alternator Output** 23 amp

(max)

**Rear Brakes** Drum **Ground Clearance** 7.1 in **Fuel Capacity** 6.3 gal

**Turning Radius** 12.8 ft

50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-**Cargo Bed Dimensions** 

(LxWxH)

800 lb (2-person)400 lb (4-person)

**Capacity** 

**DETAILS** 

**Overall Length** 

**Cargo Bed Load** 

**Payload Capacity** 

1330 lb

**Seating Capacity** 

**Towing Capacity** 1200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

2-4

128.5 in

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel** 

**Rear Suspension / Wheel Travel** 

DeDion Axle/2.8 in

**Front Tires** 23x11.00-10 **Rear Tires** 23x11.00-10

**Steering** Electric Power Steering (EPS)

**Park Brake Type** Independent, Mechanical Drum

**Front Brakes** Drum **Overall Width** 58.5 in **Overall Height** 75.8 in **Curb Weight** 1587.6 lb\* Wheelbase 85.2 in Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

**Color Choices** Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features

and more.

