MULE PRO-DX™ EPS DIESEL







P	N	V	V	F	R

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio

Fuel System Bosch in-line injection pump

Final Drive

Alternator Output

(max)

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

55 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12

Rear Tires 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions 54.1 x 53.3 x 11.0 in

(LxWxH)

Cargo Bed Load 1000 lb

Capacity

Payload Capacity 1581 lb

Seating Capacity

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1852.2 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder

lamps

Color Choices Timberline Green

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

