MULE PRO-FX™ EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83 x 2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

Double wishbone/8.5 (L) /8.7 (R) in

with differential lock

Engine Braking Ye

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension /

Wheel Travel

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions 54.1 x 53.3 x 11.0 in

1000 lb (600 lb for California models)

(LxWxH)

Cargo Bed Load Capacity

1616 lb

Payload Capacity 1

Seating Capacity 3

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1830.2 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty



