## **MULE PRO-FX™ EPS LE**







D	N	V	V	C	D
Г	u	ľ	V	Г	ĸ

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

**Bore x Stroke** 2.83 x 2.62 in

**Compression Ratio** 

**Fuel System** 

**Transmission** 

Final Drive

with differential lock

**Engine Braking** 

**Alternator Output** 

(max)

DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

**75** amp

## **CAPABILITY**

Front Suspension / Double wishbone/8.7 in **Wheel Travel** 

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 

26x9.00-12, radial 26x11.00-12, radial

**Rear Tires** 

Electric Power Steering (EPS), Tilt steering

**Park Brake Type** 

Independent, Mechanical Disc

**Front Brakes** 

Steering

**Rear Brakes** 

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

**Ground Clearance** 10.4 in

**Fuel Capacity** 7.9 gal **Turning Radius** 16.0 ft

**Cargo Bed Dimensions**  54.1 x 53.3 x 11.0 in

(LxWxH)

**Cargo Bed Load** Capacity

1000 lb (600 lb for California models)

**Payload Capacity** 1616 lb

**Seating Capacity** 3

**Towing Capacity** 2000 lb

Lighting (2) Halogen headlights. (2) LED headlights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 79.7 in

**Curb Weight** 1832.4 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

**Color Choices** Firecracker Red

Warranty Kawasaki 3-Year Limited Warranty



