
MULE PRO-FXT™ EPS CAMO









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83 x 2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Alternator Output

(max)

Engine Braking

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

Rear Tires

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Rear Brakes Dual Disc, 1 piston caliper

Dual Disc, 2 piston caliper

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions (LxWxH)

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

Cargo Bed Load

1000 lb (3-person)350 lb (6-person)(600 lb for

California models) Capacity

Payload Capacity 1616 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights. (2) LED headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

1916.1 lb* **Curb Weight**

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Realtree Xtra® Green Camo

Warranty Kawasaki 3-Year Limited Warranty



Front Brakes

