## **MULE PRO-FXT™ EPS LE**









D	N	V	V	F	R
		ш	u		м

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

**Bore x Stroke** 2.83 x 2.62 in

**Compression Ratio** 

**Fuel System** DFI® with 34mm throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 

(max)

**75** amp

## **CAPABILITY**

Front Suspension / Double wishbone/8.7 in **Wheel Travel** 

Rear Suspension / **Wheel Travel** 

**Rear Tires** 

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12, radial

26x11.00-12, radial Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

**Rear Brakes** Dual Disc, 1 piston caliper **Ground Clearance** 10.2 in

**Turning Radius** 16.0 ft

**Cargo Bed Dimensions** (LxWxH)

**Fuel Capacity** 

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

**Cargo Bed Load** 

1000 lb (3-person)350 lb (6-person)(600 lb for

California models) Capacity

7.9 gal

**Payload Capacity** 1616 lb

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 

Lighting (2) Halogen headlights. (2) LED headlights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 79.5 in

**Curb Weight** 1922.8 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

**Color Choices** Super Black, Firecracker Red

Warranty Kawasaki 3-Year Limited Warranty



