MULE PRO-MX™ EPS LE









POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load 699 lb (600 lb California models)
Capacity

Payload Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Towning capacity 1500 tb

Lighting (2) Halogen headlights. (2) LED headlights

33.4 x 44.1 x 9.1 in

CAPABILITY

Front Suspension / Double wishbone / 8.6 in Wheel Travel

Rear Suspension / Double wishbone/9.1 in Wheel Travel

 Front Tires
 25x10.00-12, radial

 Rear Tires
 25x10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Dual Disc, 2 piston caliper

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1594.2 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Color Choices Firecracker Red, Super Black

Warranty Kawasaki 3-Year Limited Warranty



Front Brakes

