MULE SX™ 4x4 XC LE FI







D	N	V	V	C	D
Г	u	ľ	V	Г	ĸ

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

22.9 amp

Engine Braking N

Alternator Output

(max)

Rear Brakes Drum

Ground Clearance 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed Dimensions (LxWxH) 35.6 x 40.9 x 9.6 in

Cargo Bed Load

Capacity

400 lb

884 lb

Payload Capacity
Seating Capacity

2

Towing Capacity

1100 lb*

3

Lighting (4) LED headlights, tail/brake lights

CAPABILITY

Front Suspension / Wheel Travel

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel Unit Swingarm/3.1 in

Front Tires 26x9.00-12
Rear Tires 26x9.00-12

Steering Rack-and-pinion, Tilt steering

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 75.0 in

Curb Weight 1098.1 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Color Choices Metallic Onyx Black

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

