NINJA® ZX™-10RR







POWER

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine**

cooled

13.0:1

Displacement 998cc

76.0 x 55.0mm **Bore x Stroke**

Compression

Ratio

Fuel System

DFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder

TCBI with digital advance and Sport-Kawasaki Ignition

Traction Control (S-KTRC)

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Intelligent Braking (KIBS), Brembo dual semi-

floating 330mm discs with dual radial mounted

monobloc 4-piston calipers

KIBS-controlled, single 220mm disc with aluminum **Rear Brakes**

single-piston caliper

DETAILS

Frame Type Aluminum perimeter

25.0° / 4.2 in Rake/Trail

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Pankl Pistons & Titanium Connecting Rods, **Special Features**

Aerodynamic Downforce Generating Devices, Rideology the App Smartphone Connectivity, TFT

Instrumentation

Color Choices Lime Green

12 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

