TERYX KRX® 1000 SPECIAL EDITION







20.3 ft

351 lbs

781 lbs

N/A

14.6 x 33.1 x 9.1 in

D	N	١	AI	Œ	Ю
Г	u	II.	n	IE	л

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999c

Maximum Torque 76.7 lb-ft @ 7000 rpm

Bore x Stroke 92.0 x 75.1 mm

Compression Ratio 11.5:

Fuel System DFI with two 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

DETAILS

Lighting

Frame

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Capacity

Dimensions (LxWxH)

Ladder type, tubular steel

(2) LED headlights, (2) LED taillights, LED stoplight

Overall Length 130.1 in

Overall Width 68.1 in

Overall Height 74.6 in

Curb Weight 1969.1 lbs (1971.3 CA)*

Wheelbase 98.8 i

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning

lamp.

Additional Features Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45

Winch

Color Choices Metallic Flat Raw Graystone

Warranty 6 Month Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in.

Rear Suspension / Wheel Travel

Front Brakes

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in.

Front Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Rear Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.7 in (std)

Fuel Capacity 10.6 gal

Scan with camera to view videos, key features and more.

